

Street Magic LED Fender Tips

- 1. Be sure bike is off.**
- 2. Remove lens using small flat head screw driver.**
- 3. Remove stock 194 bulb from socket.**
- 4. Be sure socket contacts are clean.**
- 5. Place flat head screw driver under bottom of socket and push up slightly.**
- 6. Push new LED Fender Tip into socket using back and forth motion while supporting socket with screw driver.**
- 7. It may be necessary to slightly bend the socket backwards towards the fender in order to get the lens back on with the LED Fender Tip Board.**
- 8. Reinstall Lens.**
- 9. Test Operation.**

Street Magic LED Fender Tips

- 1. Be sure bike is off.**
- 2. Remove lens using small flat head screw driver.**
- 3. Remove stock 194 bulb from socket.**
- 4. Be sure socket contacts are clean.**
- 5. Place flat head screw driver under bottom of socket and push up slightly.**
- 6. Push new LED Fender Tip into socket using back and forth motion while supporting socket with screw driver.**
- 7. It may be necessary to slightly bend the socket backwards towards the fender in order to get the lens back on with the LED Fender Tip Board.**
- 8. Reinstall Lens.**
- 9. Test Operation.**

Street Magic LED Fender Tips

- 1. Be sure bike is off.**
- 2. Remove lens using small flat head screw driver.**
- 3. Remove stock 194 bulb from socket.**
- 4. Be sure socket contacts are clean.**
- 5. Place flat head screw driver under bottom of socket and push up slightly.**
- 6. Push new LED Fender Tip into socket using back and forth motion while supporting socket with screw driver.**
- 7. It may be necessary to slightly bend the socket backwards towards the fender in order to get the lens back on with the LED Fender Tip Board.**
- 8. Reinstall Lens.**
- 9. Test Operation.**

Street Magic LED Fender Tips

- 1. Be sure bike is off.**
- 2. Remove lens using small flat head screw driver.**
- 3. Remove stock 194 bulb from socket.**
- 4. Be sure socket contacts are clean.**
- 5. Place flat head screw driver under bottom of socket and push up slightly.**
- 6. Push new LED Fender Tip into socket using back and forth motion while supporting socket with screw driver.**
- 7. It may be necessary to slightly bend the socket backwards towards the fender in order to get the lens back on with the LED Fender Tip Board.**
- 8. Reinstall Lens.**
- 9. Test Operation.**