

Street Magic™ LED Turn Signals

1. Remove lens from turn signal housing.
2. Remove bulb from turn signal housing.
3. Be sure contacts are clean.
4. Insert base of LED cluster into housing, be sure it is fully seated
5. Twist cluster to coil wire and insert cluster into housing.
6. While holding cluster in place, reinstall lens.
7. Check operation of turn signal in all modes.

Note: HD Bullet turn signals may require trimming of black gasket to fully seat lens.

Street Magic™ LED Turn Signals

1. Remove lens from turn signal housing.
2. Remove bulb from turn signal housing.
3. Be sure contacts are clean.
4. Insert base of LED cluster into housing, be sure it is fully seated
5. Twist cluster to coil wire and insert cluster into housing.
6. While holding cluster in place, reinstall lens.
7. Check operation of turn signal in all modes.

Note: HD Bullet turn signals may require trimming of black gasket to fully seat lens.

Street Magic™ LED Turn Signals

1. Remove lens from turn signal housing.
2. Remove bulb from turn signal housing.
3. Be sure contacts are clean.
4. Insert base of LED cluster into housing, be sure it is fully seated
5. Twist cluster to coil wire and insert cluster into housing.
6. While holding cluster in place, reinstall lens.
7. Check operation of turn signal in all modes.

Note: HD Bullet turn signals may require trimming of black gasket to fully seat lens.

Street Magic™ LED Turn Signals

1. Remove lens from turn signal housing.
2. Remove bulb from turn signal housing.
3. Be sure contacts are clean.
4. Insert base of LED cluster into housing, be sure it is fully seated
5. Twist cluster to coil wire and insert cluster into housing.
6. While holding cluster in place, reinstall lens.
7. Check operation of turn signal in all modes.

Note: HD Bullet turn signals may require trimming of black gasket to fully seat lens.