

Magic Brake Strobe™

1. **Locate brake wire and cut in half**
2. **Connect Red Wire to Input Side using Posi-Lock.**
3. **Connect White Wire to Output (brake light) Side using Posi-Lock.**
4. **Connect Black Wire to Ground using Posi-Tap**
5. **Secure unit with enclosed tie wraps**
6. **Select Desired Pattern with Power Off**
7. **Check Operation**
8. **To change Mode, turn bike off and change dial to desired pattern.**
(for operation of Posi, see www.posi-lock.com)

Pattern 0: Four Flashes then Solid (Incandescent or LED)

Pattern 1: Four Flashes, Solid for 3 Seconds, Repeat (Incandescent or LED)

Pattern 2: Seven Flashes then Solid (Incandescent or LED)

Pattern 3: Seven Flashers, Solid for 3 Seconds, Repeat (Incandescent or LED)

Pattern 4: Quad Strobe then Solid for 1 Second then Quad Strobe (LED Only)

Pattern 5: Quad Strobe, Solid for 1 Second, then Quad Strobe, Solid for 3 Seconds, Repeat (LED Only)

Pattern 6: Blaster X Pattern for 3 seconds, then Solid (LED Only)

Pattern 7: Constant Blaster X Pattern (LED Only)

Pattern 8: Constant Fast Strobe 5 Seconds, then Solid (LED Only)

Pattern 9: Constant Fast Strobe Pattern (LED Only)



CUSTOMLED