



## ELLIPSE MIRROR WITH FLAT GLASS 1437

**FITS: UNIVERSAL APPLICATIONS**

### PARTS INCLUDED

- 1 Left Ellipse Mirror Assembly
- 1 Right Ellipse Mirror Assembly
- 1 Hardware Kit Including:
  - 2 5/16-18 x 1-1/2" SHCS Fastener
  - 2 5/16-18 x 2" SHCS Fastener
  - 1 1/8" Allen Wrench
  - 2 5/16-18 x 5/16-24 Double-ended Stud
  - 4 5/16" Internal Tooth Lock Washer
  - 4 5/16" Split Lock Washer
- 1 Installation Instruction

*Please read and understand entire instructions before starting installation.*

### THANK YOU FOR CHOOSING KÜRYAKYN!

**IN ORDER TO PROTECT YOU AND OTHERS FROM POSSIBLE INJURY AND/OR PROPERTY DAMAGE OR LOSS, PLEASE PAY CLOSE ATTENTION TO ALL INSTRUCTIONS, WARNINGS, CAUTIONS AND ATTENTION NOTES REGARDING THE USE AND CARE OF THIS PRODUCT.**

**ATTENTION!** This indication alerts you to the fact that ignoring the contents described herein may negatively affect product performance and functionality.

**NOTE** Mirror adapters (sold separately) are required for installation on metric cruisers. For Honda, Suzuki, Kawasaki, or Victory models, use Kuryakyn P/N 1445; for Yamaha models, use Kuryakyn P/N 1446.

**NOTE** The included 1/8" Allen Wrench is only used in Part #'s: 1428, 1430, 1437 & 1438 to adjust the two fasteners which control the swivel ball tension.

### TOOLS SUGGESTED

Allen wrenches, combinations wrenches, red Loctite.

**STRICTLY OBSERVE THE FOLLOWING GUIDELINES IN ORDER TO USE THE PRODUCT PROPERLY AND AVOID POTENTIALLY DANGEROUS ACCIDENTS.**

**ATTENTION!** It is the installers' responsibility to make sure all fasteners (including pre-assembled) are tightened before operation of motorcycle. Kuryakyn will not warranty components that are lost due to improper installation. Periodic maintenance may be required.

### PROCEDURE

Remove the stock mirrors; refer to your factory service manual for specific instructions.

**-cont.-**

### CUSTOMER SERVICE

877.370.3604 (toll free)

### INSTALLATION QUESTIONS

techsupport@kuryakyn.com  
or call 715.247.2983

### LIMITED WARRANTY

Kuryakyn warrants that any Kuryakyn products sold hereunder, shall be free of defects in materials and workmanship for a period of one (1) year from the date of purchase by the consumer excepting the following provisions:

- Kuryakyn shall have no obligation in the event the customer is unable to provide a receipt showing the date the customer purchased the product(s).
- The product must be properly installed, maintained and operated under normal conditions.
- Kuryakyn makes no warranty, expressed or implied, with respect to any gold plated products.
- Kuryakyn shall not be liable for any consequential and incidental damages, including labor and paint, resulting from failure of a Kuryakyn product, failure to deliver, delay in delivery, delivery in nonconforming condition, or for any breach of contract or duty between Kuryakyn and a customer.
- Kuryakyn products are often intended for use in specific applications. Kuryakyn makes no warranty if a Kuryakyn product is used in applications other than intended.
- Kuryakyn electrical products are warranted for one (1) year from the date of purchase by the consumer. Components of Kuryakyn products containing L.E.D.s will be warranted for defects in materials and workmanship for 3 years from the date of purchase.
- Kuryakyn makes no warranty of any kind in regard to other manufacturer's products distributed by Kuryakyn. Kuryakyn will pass on all warranties made by the manufacturer and where possible, will expedite the claim on behalf of the customer, but ultimately, responsibility for disposition of the warranty claim lies with the manufacturer.

### ABOUT OUR CATALOG

You'll find all our innovations for H-D, GL and Metric Cruisers in our annual catalogs. Order online today—select the "CATALOGS" icon. Each Kuryakyn product comes with a Proof-of-Purchase good for a complimentary catalog. Details in packaging.

Be sure to ask your local dealer about other Kuryakyn products, the motorcycle parts and accessories designed for riders by riders.

©2005 Kuryakyn USA All Rights reserved.




## RIGHT AND LEFT SIDE STANDARD MOUNT

**STEP 1** Several fasteners are included with the installation kit; choose the correct fastener length for your application. Use the split washer and fastener combination that will provide the most thread engagement without bottoming out in the mirror stem.

**NOTE** Ensure that the setscrew in the mirror stem does not prevent the stud from being fully installed. See [PIC.1](#).

**STEP 2** Insert the fastener through the bottom of the hand control then through the turn signal mounting plate. Install an internal tooth lock washer over the fastener shaft then tighten the mirror stem. Tighten the setscrew to help prevent the stem from moving out of position. See [PIC.1](#).

**STEP 3** Adjust the mirrors for maximum visibility; secure the mirror head to the stem with a 5/16" wrench.



## RIGHT SIDE SWIVEL MOUNT (HARLEY-DAVIDSON MODELS ONLY)

**STEP 1** Place a dab of red Loctite on the short threaded section of one of the double-ended studs; install into the threaded hole on the bottom of the right side mirror stem. Tighten the stud; tighten the set screw at the bottom of the mirror stem against the stud.

**NOTE** Ensure that the setscrew in the mirror stem does not prevent the stud from being fully installed. See [PIC.1](#).

**STEP 2** Install an internal tooth lock washer over the remaining threaded section of the double-ended stud; insert the assembly into the hand control. Secure in place with the cupped part of the universal joint.

**STEP 3** Tighten the setscrew to help prevent the stem from moving out of position. See [PIC.1](#).

**STEP 4** While holding the turn signal in position, tighten the ball joint until it is secure.

## ADJUST BALL JOINT TENSION

**STEP 1** Remove the four fasteners from the front of the mirror cover; carefully remove the front cover and mirror glass.

**STEP 2** Turn the tension screws inside the mirror housing to increase or decrease the tension on the ball joint. Turn the screws clockwise to increase tension; turn the screws counter-clockwise to decrease tension.

**STEP 3** Replace the mirror glass and front cover, secure with the four fasteners.

*Ride On!*

**Kuryakyn®**

**PIC.1**

**SET  
SCREW**

**PAGE**

**2**

**ELLIPSE MIRRORS INSTALLATION**