



SCYTHE MIRRORS 1449

FITS: DIRECT REPLACEMENT FOR H-D APPLICATIONS, UNIVERSAL APPLICATIONS WITH PROPER ADAPTER (SOLD SEPARATELY)

PARTS INCLUDED

- 1 Left Mirror Assembly
1 Right Mirror Assembly
1 Hardware Kit, Including:
2 5/16-18 X 1-1/2" Socket Head Cap Screws
2 5/16-18 X 2" Socket Head Cap Screws
1 2.5mm Hex Key Wrench
2 5/16" Split Lock Washers
2 5/16" Internal Tooth Lock Washers
2 Double End Threaded Studs
1 Installation Instructions

Please read and understand entire instructions before starting installation.

THANK YOU FOR CHOOSING KÜRYAKYN!

IN ORDER TO PROTECT YOU AND OTHERS FROM POSSIBLE INJURY AND/OR PROPERTY DAMAGE OR LOSS, PLEASE PAY CLOSE ATTENTION TO ALL INSTRUCTIONS, WARNINGS, CAUTIONS AND ATTENTION NOTES REGARDING THE USE AND CARE OF THIS PRODUCT.

ATTENTION! This indication alerts you to the fact that ignoring the contents described herein may negatively affect product performance and functionality.

TOOLS SUGGESTED

A full set of standard hex key and combination wrenches.

STRICTLY OBSERVE THE FOLLOWING GUIDELINES IN ORDER TO USE THE PRODUCT PROPERLY AND AVOID POTENTIALLY DANGEROUS ACCIDENTS.

NOTES

Mirror adapters (sold separately) are required on metric cruiser. For Honda, Suzuki, Kawasaki, or Victory models use Kuryakyn P/N 1445; for Yamaha models use Kuryakyn P/N 1446.

You may choose to use medium strength thread lock on the supplied fasteners prior to installation.

PROCEDURE FOR PERCH MOUNT TURN SIGNALS

STEP 1 Read and understand all steps in the instructions before starting the installation. Park the motorcycle on a hard, level surface and turn off the ignition.

STEP 2 Remove stock mirrors. Pay close attention to how the stock turn signal ball joint assembly comes apart as this will aid in re-assembly.

-cont.-

CUSTOMER SERVICE
877.370.3604 (toll free)

INSTALLATION QUESTIONS
techsupport@kuryakyn.com
or call 715.247.2983

LIMITED WARRANTY
Kuryakyn warrants that any Kuryakyn products sold hereunder, shall be free of defects in materials and workmanship for a period of one (1) year from the date of purchase by the consumer excepting the following provisions:

- Kuryakyn shall have no obligation in the event the customer is unable to provide a receipt showing the date the customer purchased the product(s).
- The product must be properly installed, maintained and operated under normal conditions.
- Kuryakyn makes no warranty, expressed or implied, with respect to any gold plated products.
- Kuryakyn shall not be liable for any consequential and incidental damages, including labor and paint, resulting from failure of a Kuryakyn product, failure to deliver, delay in delivery, delivery in non-conforming condition, or for any breach of contract or duty between Kuryakyn and a customer.
- Kuryakyn products are often intended for use in specific applications. Kuryakyn makes no warranty if a Kuryakyn product is used in applications other than intended.
- Kuryakyn electrical products are warranted for one (1) year from the date of purchase by the consumer. Components of Kuryakyn products containing L.E.D.s will be warranted for defects in materials and workmanship for 3 years from the date of purchase.
- Kuryakyn makes no warranty of any kind in regard to other manufacturer's products distributed by Kuryakyn. Kuryakyn will pass on all warranties made by the manufacturer and where possible, will expedite the claim on behalf of the customer, but ultimately, responsibility for disposition of the warranty claim lies with the manufacturer.

ABOUT OUR CATALOG
You'll find all our innovations for H-D, GL and Metric Cruisers in our annual catalogs. Order online today--select the "CATALOGS" icon. Each Kuryakyn® product comes with a Proof-of-Purchase good for a complimentary catalog. Details in packaging.

Be sure to ask your local dealer about other Kuryakyn® products, the motorcycle parts and accessories designed for riders by riders.

©2005 Kuryakyn USA® All Rights reserved.



STEP 3 Insert a supplied Double End Threaded Stud through the mirror-mounting hole of the perch with longest portion of threads through the perch.

STEP 4 Place a supplied 5/16" Internal Tooth Lock Washer on the upward facing threads of the Double End Threaded Stud. Thread the mirror stem tightly onto the stud. Use a 3/8" open-end wrench to hold the flange of the stud while the mirror is tightened and positioned.

STEP 5 Reinstall the turn signals in the reverse manner as they were removed with a supplied 5/16" Split Lock Washer between the perch and the turn signal assembly. Be careful not to strip the threads on the ball receptacle.

STEP 6 Position the mirror for best rearward visibility.

STEP 7 Tighten set screw to secure mirror to the stud.

ATTENTION! It is the installer's responsibility to ensure that all of the fasteners (including pre-assembled) are tightened before operation of the motorcycle. Küryakyn will not warranty components lost due to improper installation. Periodic maintenance may be required.

PROCEDURE FOR NON- PERCH MOUNT TURN SIGNALS

STEP 1 Read and understand all steps in the instructions before starting the installation. Park the motorcycle on a hard, level surface and turn off the ignition.

STEP 2 Remove stock mirrors.

STEP 3 Choose the longest Allen bolt from the hardware kit that will provide maximum thread engagement into the mirror stem without bottoming out, either the 5/16"-18 X 1-1/2" or the 5/16"-18 X 2" Socket Head Cap Screw. Insert the Socket Head Cap Screw of choice from the bottom of the perch upward with a supplied 5/16" Split Lock Washer installed between the head of the fastener and the perch.

STEP 4 Place a supplied 5/16" Internal Tooth Lock Washer on the threads of the Socket Head Cap Screw on the topside of the perch. Thread the Socket Head Cap Screw into the mirror stem tightly using a 1/4" hex key wrench.

STEP 5 Position the mirror for best rearward visibility.

STEP 6 Tighten set screw to secure Mirror to the stud.

ATTENTION! It is the installer's responsibility to ensure that all of the fasteners (including pre-assembled) are tightened before operation of the motorcycle. Küryakyn will not warranty components lost due to improper installation. Periodic maintenance may be required.

Ride On!

FIG.

