



Custom Dynamics® ProBEAM®
Indian Scout Replacement Lenses
Installation Instructions

We thank you for purchasing the Custom Dynamics® ProBEAM® Indian Scout Replacement Lenses! Our LEDs offer maintenance free service and higher visibility. Our ProBEAM® product line utilizes the latest technology and automotive grade components to ensure the highest level of reliable service. Custom Dynamics® offers one of the best warranty programs and customer support in the industry. If you have any questions during the installation of this product please call us at 1(800) 382-1388.

Part Numbers:

PB-SCOUT-AMBER PB-SCOUT-RED PB-SCOUT-SMOKE

Package Contents:

- ProBEAM® PB-SCOUT-LENS (2)
- Instructions

Fitment: Replaces OEM front & rear turn signal lenses on 2015-2020 Indian® Scout & Scout Sixty models (Does not fit Scout Bobber models).



Please read all Information below before Installation

Warning: Disconnect negative battery cable from battery; refer to owner's manual. Failure to do so may result in electrical shock, injury, or fire. Secure negative battery cable away from positive side of battery and all other positive voltage sources on vehicle.

Safety First: Always wear appropriate safety gear including safety glasses when performing any electrical work. It is highly recommended that safety glasses be worn throughout this installation process. Be sure vehicle is on level surface, secure and cool.

Important: This product is designed and intended for use as auxiliary lighting only. It is NOT intended to replace any original equipment lighting installed on the vehicle and should not be used for that purpose. This product must be wired so that it does not interfere with any original equipment lighting.

Installation:

1. Locate the 2 Philips screws in the face of the turn signal.
2. Hold the lens as you remove the 2 Philips screws (keep the screws you will need them to install the new lens).
3. Clean any dirt or grime from housing.
4. Installing the lens on the housing, make sure the rubber gasket sits flush to the housing.
5. Reinstall the 2 existing Philips head screws. Overtightening the lens will cause the lens to crack.

Questions? Call us at: 1 (800) 382-1388 M-TH 8:30AM-5:30PM / FR 9:30AM-5:30PM EST