



DHD2 LENS Installation Instructions

We thank you for purchasing the DHD2 Lens. The DHD2 Lens utilize the latest technology and high quality components to ensure you the most reliable service. We offer one of the best warranty programs in the industry and we back our products with excellent customer support. If you have questions before or during installation of this product, please call Custom Dynamics® at 1(800) 382-1388.

Chris Products®

Part Number: DHD2A DHD2C
DHD2R DHD2S

Package Contents:

- DHD2 (1)

Fitment: 1986-2001 Harley-Davidson® FXS, FXL, FXD, FXR, FDWG, and XL Models.

Stock OEM Old Bullet Style signals lenses with 2 screws.

Installation:

1. Remove old lens using a Phillips head screwdriver.
2. Locate the two Philips head screws on the lens.
3. Remove one screw at a time. Hold the lens as you remove screws. (Keep screws you will need them to reinstall new lens).
4. Clean any dirt or debris from turn signal housing.
5. Install lens on housing making sure to line up screws holes (hold lens in place). Using the two Phillips head screws you removed early, install one screw at a time. Do not over tighten screws this could cause the lens to crack.



Please read all Information below before Installation



ATTENTION



Safety First: Make sure the bike is parked on a level surface and bike's mechanical components are cool to the touch.



Questions? Call us at: 1 (800) 382-1388 M-TH 8:30AM-5:30PM / FR 9:30AM-5:30PM EST